

QUANTERRA Q330


LOW-POWER HIGH RESOLUTION NETWORK-AWARE SEISMIC SYSTEM



General Description

The Q330 is an advanced 3 or 6 channel broad-band, high resolution seismic system incorporating Quanterra's proven IP networking technology into a very low-power field package. The Q330 uses Quanterra's exclusive patented (US Patent 4866442, Japan Patent 2787445, others pending) ultra-low-power delta-sigma 24-bit A/D with DSP, and includes 8Mb RAM, GPS receiver, power management, sensor command/control, and an advanced telemetry application for reliable data delivery.

Telemetry...



...and Local Recording



The Q330 supports real-time data telemetry to a central site or connection via hard-wire or radio (burst or continuous) to a local low-power recording system, or both simultaneously.

Low! Power

Incorporating the latest low-power technology, the Q330 achieves integrated capability with an average power requirement of <0.75Watt, including recorder & GPS!

Internet-Ready Industry Standards

The telemetry protocols uses industry standard stateless IP communications, enabling the use of off-the-shelf IP equipment and service providers. Serial IP and Ethernet 10BaseT are built-in.

Comprehensive Sensor Control

The Q330 is a seismological instrument, not a digitizer alone. Sensor control interface, including calibration, and sensor identification-tag support is built in.

Streamlined Remote Administration

The Q330 is designed for simple network maintenance and administration, before, during, and after deployment. Internet security is built-in.

Specifications

| Specification | Description |
|---------------------------|---|
| Channels | standard 6-channel Q330-6 |
| Auxiliary Channels (Opt.) | 4/8 DI/SE 16-bit 1sps. Full scale range $\pm 50V$ |
| Dynamic Range | 132-135 dB wideband RMS typical. Typical band-limited 136 dB |
| Format | 32-bit integer, Level 2 compressed 1-second packets |
| Input Range | 40V P-P at gain=1 |
| Gain | Selectable per channel: 1,30 |
| Filtering | Linear or Minimum Phase FIR. |
| Sample Rate | 200, 100, 50, 40, 20, 10, 1 Other rates available. |
| Time Base | Precision TCXO, locked to GPS. No adjustment. |
| DSP/CPU | ADSP-2189M |
| Telemetry | Full Duplex, efficient positive acknowledge with error control. UDP/IP over serial and Ethernet. Burst or continuous. Operates with major application software. |
| Temperature | Fully specified -20 to +50C Operative -40 to +70C |
| Sensor Control | Calibrate step, sine, or random. Recenter, on-command |
| Operational Data | Temp, DC voltage, GPS status, Sensor boom position (6 chan) |
| Memory | 32Mb RAM standard |
| Network | IEEE 802 10Base-T Ethernet UDP/IP Protocol Stack |
| Serial Ports | 2 serial telemetry and 1 console ports up to 115kbaud. |
| Wireless | IrDA interface supported. |
| Power | <0.6 W avg. 12VDC 3-channel <0.8 W avg. 12VDC 6-channel |
| Physical | Sealed, Aluminum, 14 X 4 X 6 in., 8 lbs., Rubber endcaps, Externally visible status and fault indicators. |

Q330 - QUANTERRA, INC. - 2 Shaker Rd, Ste. F 200, Shirley, MA 01464, USA 978-425-2100

SPECIFICATIONS SUBJECT TO CHANGE

Rev L.